



Elektro-Automatik

Why should I choose for an EA-PS 9000 1U?

Advantages:

- Auto-ranging Output: Compared to power systems with conventional (rectangular) output characteristic, the auto-ranging feature allows to power a much larger number of devices (EUTs) with different nominal voltages
- Highest power density: 19" 1U rack format providing for 3000W of DC output power from a 230V~ 16A single-phase mains supply.
- Highly isolated structure, therefore much less sensitive against disturbances under operation (high electro-magnetic immunity to industrial environment standard, high reliability)
- EMI compliant to EN 61000-6-3, EN 55022 class B (meets EMI requirement for residential-, commercial- and light-industrial environment)
- Fast discharge of output capacitance to IEC 1010 (high user safety, output voltage will decrease to <60VDC (low-voltage safety directive) in < 10 sec. even under no-load condition)
- Standard on-board 3-way interface: Analogue 0-5V/0-10V, USB, Ethernet/LAN or GPIB (all galvanically isolated)
- DOT Matrix Display showing set and true values at the same time
- Self-calibration function: User may measure deviation values himself and key in the correction values into the menu to restore ex-factory precision
- High-performance micro-processor LPC 1778 (Cortex M3) allowing up to 10 times faster programming-reaction time
- Alarm Manager (limits adjust) for OVP, OCP, OPP
- High resolution of up to 16 Bit (very fine programming and read-back steps)
- Voltage accuracy 0.1% of nominal
- Professional user control software for up to 20 devices (license fee applies)
- Safety compliant to IEC/EN 61010